

ANYSOL D80

NAME OF PARAMETER	UNIT	TESTING METHOD	RESULTS
APPEARANCE		VISUAL	BRIGHT & CLEAR
DENSITY (15°C)	g/cm ³	ASTM D4052	0.7995
SP. GR. (15°C)		ASTM D4052	0.8002
WATER CONTENT	WT.PPM	ASTM D1744	20
POUR POINT	°C	ASTM D97	-42.0
VISCOSITY, (20°C)	mm ² /s(cSt)	ASTM D445	2.39
VISCOSITY, (40°C)	mm ² /s(cSt)	ASTM D445	1.68
CU-CORROSION (100°C, 3HR)		ASTM D130	1B
BROMINE INDEX	mg/100g	ASTM D2710	1.00
BENZENE	wt. ppm	ASTM D6229	0.0
TOTAL AROMATICS	wt. ppm	UOP 495	11.00
SULFUR	wt. ppm	ASTM D5453	LESS THAN 1.00
SAYBOLT COLOR		ASTM D156	+30
ANILINE POINT	°C	ASTM D611	75.7
FLASH POINT	°C	ASTM D93	83.5
DISTILLATION, IBP	°C	ASTM D86	212.0
DISTILLATION, 5%	°C	ASTM D86	214.9
DISTILLATION, 10%	°C	ASTM D86	215.1
DISTILLATION, 50%	°C	ASTM D86	217.9
DISTILLATION, 90%	°C	ASTM D86	224.8
DISTILLATION, 95%	°C	ASTM D86	228.2
DISTILLATION, DP	°C	ASTM D86	233.6