

BO BS150 COA

Test Parameters	Test Method	Spec	Results
Appearance	Visual	Bright & Clear	Bright & Clear
ASTM Color	ASTM D 1500	6.0 Max	L 2.0
Specific Gravity@ 60/60 deg. F	ASTM D 4052	Report	0.9038
Density@ 15 deg. C, g/cm ³	ASTM D 4052	Report	0.9032
Density@ 15 deg. C, g/cm ³	ASTM D 4052	Report	0.8938
Flash Point (COC), deg. C	ASTM D 92	282 Min	324
Pour Point, deg. C	ASTM D 5950	-6 Max	-6
Kinematic Viscosity @ 40 deg. C, cSt	ASTM D 445	Report	511.6
Kinematic Viscosity@ 100 deg. C, cSt	ASTM D 445	30.0 – 35.0	32.54
Viscosity Index	ASTM D 2270	95 Min	95
Corrosion Copper Strip (3 Hours / 100 deg. C)	ASTM D 130	1 Max	1b
Total Acid Number, mg KOH/g	ASTM D 664	0.05 Max	0.01
Micro Method carbon residue, % wt	ASTM D 4530	0.8 Max	0.44
Sulfur Content, % wt	ASTM D 4294	Report	0.596
Water Content, % vol	ASTM D 95	Nil	Nil