

BO SN 500 COA

PROPERTIES	SPEC	METHOD	RESULTS
APPEARANCE	B/C	VISUAL	BRIGHT & CLEAR
ACID NUMBER, MG.KOH/G	MAX 0.05	ASTM D 664	0.01
ASTM COLOR	MAX 2.5	ASTM D 1500	0.5
DENSITY @ 15 DEG.C, KG/L	REPORT	ASTM D 4052	0.8862
DENSITY @ 30 DEG.C, KG/L	REPORT	ASTM D 4052	0.8767
KINEMATIC VISCOSITY @ 40 DEG.C, CST	REPORT	ASTM D 445	100.3
KINEMATIC VISCOSITY @ 100 DEG.C, CST	10.75-11.25	ASTM D 445	11.21
VISCOSITY INDEX	MIN 95	ASTM D 2270	97
TOTAL SULFUR CONTENT, MASS%	MAX 0.6	ASTM D 4294	0.359
FLASH POINT, DEG.C	MIN 237	ASTM D 92	258
CARBON RESIDUE, MICRO METHOD, %(M/M)	MAX 0.15	ASTM D 4530	0.06
WATER CONTENT, %	MAX 0.05	ASTM D 95	0.00
ANILINE POINT, DEG.C	REPORT	ASTM D 611	109.75
POUR POINT, DEG.C	MAX -9	ASTM D 97	-9